

# MIPOLAM® AMBIANCE ULTRA™

gerflor.com  
gerflor.asia

**Mipolam® Ambiance Ultra™** is a homogeneous pressed compacted floorcovering in sheet, with non-directional design, colour dyed as a raw mixture to ensure even color throughout the thickness and a matt finish. Its surface is densely compacted for improved wear and ease of maintenance.

It is treated with Evercare™, the latest improvement in polyurethane special maintenance treatment obtained by UV laser crossing-linking. Evercare™ avoids staining of chemical products, like betadine, eosin, or anti-bacterial hand gel and increases the durability of the flooring. No wax for life!

**Mipolam® Ambiance Ultra™** incorporates bacteriostatic and fungistatic actions. The flooring complies with the EN 649 (34-43) and has a Group T wear rating. It is suitable for very heavy traffic areas.

**Mipolam® Ambiance Ultra™** is available in a wide pallet of 50 classic and trendy colors.

## MIPOLAM® AMBIANCE ULTRA™

DESCRIPTION			
Total thickness	ISO 24346 [EN 428]	mm	2
Weight	ISO 23997 [EN 430]	g/m <sup>2</sup>	2750
Width of sheet	ISO 24341 [EN 426]	cm	200
Length of sheet	ISO 24341 [EN 426]	lm	20
CLASSIFICATION			
Norm / Product specification	-	-	ISO 10581 [EN 649]
European classification	ISO 10874 [EN 685]	class	34 - 43
Fire rating	EN 13 501-1	class	Bfl-s1
Static electrical propensity	EN 1815	KV	< 2
Electrical resistance	EN 1081	Ω	10 <sup>9</sup> -10 <sup>10</sup>
Slip resistance dry	EN 13893	-	≥ 0.3
Slip resistance wet	DIN 51130	class	R9
PERFORMANCES			
Wear resistance	EN 660.2	mm <sup>3</sup>	≤ 2.0
Wear group	EN 649	group	T
Type binder content	ISO 10581	type	I
Dimensional stability	ISO 23999 [EN 434]	%	≤ 0.4
Residual indentation	ISO 24343-1 [EN 433]	mm	≈ 0.03
Castor chair test	ISO 4918 [EN 425]	-	OK
Thermal conductivity	ISO 10456 [EN 12524]	W/(m.K)	≈ 0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 [EN 423]	-	OK
Anti-bacterial and fungicidal treatment	-	-	OK
Surface treatment	-	-	Evercare™
Anti-bacterial activity (E. coli - S. aureus - MRSA) <sup>[1]</sup>	ISO 22196	-	>99 % Inhibits growth
Color number	-	-	50
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/m <sup>3</sup>	< 10
Certification	-	-	Floorscore™
CE MARKING			
CE	EN 14041	-	

[1] The implementation of an effective cleaning regime is the most important defence against infections.

**Gerflor** Don't forget our complementary ranges!



## MIPOLAM® AMBIANCE ULTRA™, LESS SPEAKING FOR MORE ACTIONS

<p><b>COMPOSITION</b> 100% REACH compliant</p>	<p><b>INDOOR AIR QUALITY</b> 100 times lower than norm requirements (TVOC &lt; 10µg/m<sup>3</sup> after 28 days)</p>	<p><b>RECYCLED CONTENT</b> 100% REACH compliant recycled content</p>	<p><b>RECYCLABILITY</b> 100%</p>	<p><b>LCA</b> Eco-designed according to a product specific life cycle analysis</p>	<p><b>WELLNESS</b> Walking comfort: &lt; 75dB</p>
--	--	--	--------------------------------------	--	---

Be connected!



#Gerflor



www.gerflor.com

**Gerflor**  
theflooringgroup

GERFLOR ASIA Tel.: + 86-21-63578818

MAR 2018-03-15 Version - Indicative documentation cost USD 4.6  
Gerflor® has a policy of continuous product improvement, it reserves the right to change design and specifications without notice.