

TECNICAL DATA SHEET

Produced by weaving threads of vinyl material, INTRECCIO is a highly resistant flooring that combines modern design and ease of installation. Particularly suitable for high-traffic areas such as offices, hotels or shops that require easy maintenance flooring with an appealing appearance.

Classification

Typology	EN 10581	Woven PVC
Commercial classification	EN ISO 10874	33 Heavy

Technical features

Total thickness	EN 24346	2,5 mm
Weight	EN 23997	2,7 kg/sqm
Pattern		decorative fabric
Surface		textured

Performance

Fire reaction	EN 13501-1	Bfl-s1
Coefficient of friction	EN 13893	DS Class
Static electrical propensity	EN 1815	< 2kV (Antistatic)
Light resistance	ISO 105-B02	> 6
Dimensional stability	ISO 2551	≤ 0,25%
Bending	EN 434	< 2 mm
Thermal resistance	ISO 8302	Suitable for underfloor heating
Acoustic insulation	EN 10140	ΔLw 11DB
Castor chair	EN 985	Continuous use

Indoor air quality and environment

Formaldehyde emission	ASTM D6007-14	N. 1911060065HF-004
REACH regulation		N. 200907002SHF-006
Smoke density	ASTM E662	< 450

Format and dimensions

Sheets	EN 24341	2 x 20 m
--------	----------	----------

