




TECHNICAL DATA SHEET - TOPWELL 10 EXTRA




grooved PVC / aluminium scraper / textile



grooved PVC / Y-shaped aluminium



textile / Y-shaped aluminium



The foundation of TOPWELL 10 mm EXTRA mats are 27 mm wide aluminium sections connected by a stainless steel wire and separated by rubber rings, which make it possible to roll the mat for easier handling when cleaning.

The aluminium sections can be infilled with grooved PVC or textile strips are inserted into the aluminium sections, and can be combined with aluminium scrapers where necessary.

Infills can be combined as required and replaced when worn out. Not suitable for revolving doors.

Fire-resistant version

TOPWELL 10 mm EXTRA mats can be used for emergency exits with a fire-resistant infill and are certified according to EN 13501-1+A1:2010.

Reaction to fire certification: Bfl-s1



Technical parameters

Design:	grooved PVC strip, textile strip, aluminium scraper
Dimensions:	according to the client's requirements
Height:	10 mm
Weight:	11 kg/m ²
Installation:	at floor level in a 13 × 30 × 3 mm L-frame or freely placed on the floor with a 45 mm wide tapered aluminium frame
Resistance:	maximum load 2.5t/100 cm ²
Use:	entrance areas to hotels, banks, restaurants, office buildings, as well as family homes