



Heathstar

The Elemental Collection




Style (Méthode de fabrication/ Herstellungsverfahren/ Descripción)	Tufted 1/10" Loop Pile
Yarn Construction (Couche d'usure/ Polmaterial/ Composición fibra)	100% ECONYL® Solution Dyed Nylon manufactured from recycled fishing nets
Yarn Recycled Content (Contenu velours recyclé/ Recycler Garnanteil/ Contenido de hilo reciclado)	100%
Total Recycled Content (Contenu recyclé total/ Gesamtrecyclinganteil/ Contenido total reciclado)	79%
Pile Yarn Weight (Poids du velours/ Poleinsatzgewicht)	730gsm
Pile Height (Epaisseur du velours/ Polhöhe)	4mm
Total Weight (Poids total/ Gesamtgewicht)	4220gsm
Total Thickness (Epaisseur totale/ Gesamtdicke)	7mm
Backing (Dossier standard/ Standardrückenausstattung)	100% Envirobase - contains over 75% recycled materials
Additional Acoustic Backing (Dossier acoustique supplémentaire/ Zusätzliche/ Akustikrückenausstattung/ Respaldo acústico adicional)	Komfort Bac available on request
Tile Size & Packaging (Dimension & Emballage/ Abmessung & Verpackung/ Tamaño & Embalaje)	50cm x 50cm
Tiles Per Box	20 (5m ²)
Wear Classification (Classement d'usage/ Beanspruchungsbereich)	Heavy Contract Class 33
Luxury Class (Classement de confort/ Komfortklasse)	LC2
Anti-Static Behaviour (Antistatique/ Antistatisch)	Suitable for use with computers. Less than 2Kv
Colour Fastness (Light) (Solidité des couleurs à la lumière/ Lichtechtheit)	>6
Colour Fastness (Shampoo) (Solidité des couleurs au shampooing/ Farbechtheit (Shamponieren))	4-5
Colour Fastness (Dry Rubbing) (Solidité des couleurs au frottement à sec/ Reibechtheit (Trocken))	4-5
Colour Fastness (Wet Rubbing) (Solidité au frottement au mouillé/ Reibechtheit (Nass))	4-5
Flammability BS 4790 Hot Metal Test (Tenue au feu/ Brandverhalten/ Inflamabilidad)	≤ 35mm Low Radius of Char
Flammability- BS EN 13501 (Tenue au feu/ Brandverhalten/ Inflamabilidad)	Bfl-s1
Castor Chair Rating (Emploi chaise à roulettes/ Stuhlrolleneignung/ Idoneo para el uso con sillas de ruedas)	r ≥ 2.4 Suitable for intensive use with castor chairs
Impact Sound (Réduction du bruit d'impact/ Trittschallverbesserungsmaß/ Aislamiento a los ruidos de impactos)	Minimum 26dB
Warranty (Garantie/ Garantie)	10 years
VOC Content (Contenu en COV/ VOC-Gehalt/ Contenido de COV)	E1 (EN 14041:2004)


This Paragon product is EPD verified in accordance with ISO 14025 and EN 15804



Broadloom





Tessellated



Random Lay

Please note, for technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Paragon Carpet Tiles reserves the right to change or modify product specifications without giving prior notice.



To place your order

+44 (0)1709 763800 | sales@paragon-carpets.co.uk

More information & samples

paragon-carpets.co.uk | samples@paragon-carpets.co.uk

Paragon Carpet Tiles

Farfield Park, Manvers, Wath-upon-Dearne, Rotherham, United Kingdom S63 5DB

